Carpet Tile

City Star Acoustic

Specifications:

















Solution dyed nylon

Acoustical Noise Reduction

n

Antistatic covering

Fade resistant

Castor wheel resistant

Multi-level loop Construction -Fibre -100% Solution Dyed Nylon 1/12" Gauge -Stitches -10 per inch 23 oz/vd^2 Pile weight -Average pile height -4 mm ± 0.5 mm Backing -Mix-bac Tile size -50 cm x 50 cm Sound Absorption -BS EN ISO 354 Absorption Coefficient - NRC = 0.30 BS EN ISO 10140-3 Traffic classification -Class II, Heavy Commercial Antimicrobial -Ultra-Fresh Quarter Turn; Monolithic; Brick; Ashlar Installation method -Fire test -Class I **Pass** 8.6 kW/m2 Critical Radiant Flux - AS ISO 9239-1:2003 ≤3.5 kV Anti-static - AATCC 134 **Pass** Wear tests -Hexapod Drum Test ASTM D5252 3 Pass R=2.8 Castor Chair BS EN 985 **Pass** Stability -Delamination ASTM S3936 No Separation **Dimensional Stability AACHEN** Warranties -15 Year Wear Resistance Limited Warranty 15 Year Delamination Limited Warranty 15 Year Dimensional Stability Limited Warranty 15 Year Castor Chairs Limited Warranty 15 Year Stain Limited Warranty Life-time Static Limited Warranty

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz 10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand robertmalcolm.co.nz

