

Commercial Vinyl Forum Plus

Specifications:




Commercial
very heavy




Industrial
heavy



Slip
resistant



Dimensional
stability



Light
fastness



Thermal
resistance



Chemical
resistant



Level of use ISO 10874 -	34 – 43
Total thickness -	2.00 mm
Wear layer -	0.70 mm
Wear layer PUR treatment -	TopClean
Total weight -	3000 g/m ²
Width -	2 m
Standard length -	23 m
Inflammability EN ISO 13501-1 -	Bfl-s1
Critical radiant flux ISO 9239.1:2010 -	8.2 KW/m ²
Slip resistance DIN 51130 -	R10
Residual indentation EN ISO 24343-1 -	≤ 0.10 mm
Furniture leg resistance EN ISO 16581 -	No damage
Electrostatic properties EN 1815 -	< 2 kV on concrete
Dimensional stability EN ISO 23999 -	≤ 0.10 %
Light fastness EN ISO 105-B02 -	≥Level 6
Underfloor heating -	Suitable
Chemical resistance -	Not affected
Environmental -	Global Green Tag Level A
Formaldehyde group EN 717-1 -	E1
Total VOC emissions EN 16516 -	Gold
Warranty (year) -	10 years

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

