

# Commercial Vinyl Pioneer

## Specifications:



Commercial  
very heavy




Industrial  
heavy




Slip  
resistant




Thermal  
resistance



Dimensional  
stability



Light  
fastness



Stocked in  
New Zealand

Level of use EN ISO 10874 -	34 – 43
Total thickness -	2.50 mm
Wear layer -	0.70 mm
Wear layer PUR treatment -	PUR SHIELD
Total weight -	2250 g/m <sup>2</sup>
Width -	2 m
Standard length -	25 m
Inflammability EN 13501 -	Bfl-S1
Slip resistance EN 13893 -	DS
Slip restraint DIN 51130 -	R10
Residual indentation EN ISO 24343-1 -	≤ 0.20 mm
Dimensional stability EN ISO 23999 -	≤ 0.40 %
Light fastness ISO 105- B02 -	≥ 6
Underfloor heating -	Suitable
Warranty -	5 years Commercial 15 years Residential

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz



robert malcolm

