

# Commercial Vinyl Forum Plus

## Specifications:




Commercial  
very heavy




Industrial  
heavy



Slip  
resistant



Dimensional  
stability



Light  
fastness



Thermal  
resistance



Chemical  
resistant



Level of use ISO 10874 -	34 – 43
Total thickness EN ISO 24346 -	2.00 mm
Wear layer EN ISO 24340 -	0.70 mm
Wear layer PUR treatment -	TopClean
Total weight EN ISO 23997 -	3000 g/m <sup>2</sup>
Width -	2 m
Standard length -	23 m
Inflammability EN ISO 13501-1 -	Bfl-s1
Critical radiant flux NF EN ISO 9239.1 -	8.52 kW/m <sup>2</sup>
Slip resistance DIN 51130 -	R10
Residual indentation EN ISO 24343-1 -	≤ 0.10 mm
Furniture leg resistance EN 424 -	No damage
Electrostatic properties EN 1815 -	< 2 kV on concrete
Dimensional stability EN ISO 23999 -	≤ 0.10 %
Light fastness EN ISO 105-B02 -	≥Level 6
Underfloor heating -	Suitable
Chemical resistance -	Not affected
Environmental -	Global Green Tag Level A
Formaldehyde group EN 717-1 -	E1
Total VOC emissions EN 16516 -	Gold
Warranty (year) -	10 years

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz



robert malcolm

