

# Residential Vinyl Atlantic


## Specifications:



Domestic  
light




Slip  
resistant




Light  
fastness



Great for  
families



Stocked in  
New Zealand



Long  
lasting



Natural  
feel

European classification EN ISO 10874 -	21
Total thickness -	2.00 mm
Wear layer -	0.15 mm
Wear layer treatment -	PU laquer
Total weight -	1200 g/m <sup>2</sup>
Width -	2 m
Standard length -	32 m
Slip resistance DIN 51130 -	R10
Inflammability EN 13501-1 -	Bfl/S1
Critical Radiant Flux ISO 9239-1 -	8.1kW/m <sup>2</sup>
Acoustical insulation -	10 dB
Light fastness EN ISO 105 B02 -	≥ 6
Underfloor heating -	Suitable
Dimensional Stability EN ISO 23999 -	≤ 0.40%
Residual Indentation EN ISO 24343-1 -	≤ 0.35 mm
Warranty (year) -	5 years

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz



robert malcolm

