

# Commercial Vinyl Forum Plus

## Specifications:




Commercial  
very heavy




Industrial  
heavy



Slip  
resistant



Dimensional  
stability




Light  
fastness



Thermal  
resistance



Chemical  
resistant



10  
year guarantee

Level of use -	34 – 43
Total thickness -	2.00 mm
Wear layer -	0.70 mm
Wear layer PUR treatment -	TopClean
Total weight -	3000 g/m <sup>2</sup>
Width -	2 m
Standard length -	23 m
Inflammability -	8.2 KW/m <sup>2</sup>
Slip resistance -	R10
Residual indentation -	≤ 0.10 mm
Furniture leg resistance -	No damage
Electrostatic properties -	< 2 kV on concrete
Dimensional stability -	≤ 0.10 %
Light fastness -	≥ Level 6
Underfloor heating -	Suitable
Chemical resistance -	Not affected
Environmental -	Global Green Tag Level A
Warranty (year) -	10 years

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz



robert malcolm