Residential Vinyl

Belgo

Specifications:

















Domestic heavy

Commercial moderate

Slip resistant

Reduces

Thermal

Great for

Stocked in

Protectonite PU

European classification EN ISO 10874 -	23 – 32
Total thickness -	2.60 mm
Wear layer -	0.35 mm
Wear layer treatment -	PU / Natural Feel
Total weight -	1800 g/m²
Width -	3 m
Standard length -	25 m or 30 m
Slip resistance DIN 51130 -	R10
Inflammability EN 13501 -	Cfl-S1
Acoustical insulation ISO 717 -	18 dB
Underfloor heating -	Suitable
Thermal conductivity EN 12524 -	0.25 W / mK
Thermal resistance EN ISO 12466 -	0.0104 m² K/W
Resistance to household chemicals -	Very good
Warranty -	15 years

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 **e** office@robertmalcolm.co.nz 10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand **robertmalcolm.co.nz**

