

Carpet Tile

London


Specifications:



Solution dyed nylon



Antistatic covering



Fade resistant



Castor wheel resistant



| | | |
|--|--|------|
| Construction - | Multi-level Loop | |
| Fibre - | 100% Solution Dyed Nylon | |
| Gauge - | 1/12" | |
| Stitches - | 13 per inch | |
| Average pile height - | 4 mm ± 0.5 mm | |
| Total height - | 7 mm ± 0.5 mm | |
| Backing - | Eco Ace Backing | |
| Tile size - | 50 cm x 50 cm | |
| Traffic classification - | Commercial - Heavy Duty | |
| Antimicrobial - | Ultra-Fresh | |
| Critical Radiant Flux AS ISO 9239-1:2003 - | 6.4 kW/m ² | |
| Anti-static AATCC134 - | ≤3.5 kV | Pass |
| Wear tests | | |
| Hexapod drum test ASTM D5252 - | 3 | Pass |
| Castor chair BS EN985 - | r =2.8 | Pass |
| Stability | | |
| Delamination ASTM D3936 - | No Separation | |
| Dimensional Stability AACHEN - | ≤ 0.2 | Pass |
| Warranties - | | |
| | 15 Year Wear Resistance Limited Warranty | |
| | 15 Year Delamination Limited Warranty | |
| | 15 Year Dimensional Stability Limited Warranty | |
| | 15 Year Castor Chairs Limited Warranty | |
| | 15 Year Stain Limited Warranty | |
| | Life-time Static Limited Warranty | |

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under castor wheels to protect the appearance retention of the product and to avoid excessive wear in these areas.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz

robert malcolm

