## Carpet Tile Mineral Acoustic

## **Specifications:**

Solution Acoustical Antistatic Fade dyed nylon Noise Reduction covering resista	Gut TM Gert TM
Construction -	Multi-level loop
Fibre -	100% Solution Dyed Nylon
Gauge -	1/12"
Stitches -	10 per inch
Pile weight -	23 oz/yd <sup>2</sup>
Average pile height -	4 mm ± 0.5 mm
Backing -	Mix-bac
Tile size -	50 cm x 50 cm
Sound Absorption -	BS EN ISO 354 Absorption Coefficient – NRC = 0.30
	BS EN ISO 10140-3
Traffic classification -	Class II, Heavy Commercial
Antimicrobial -	Ultra-Fresh
Installation method -	Quarter Turn; Monolithic; Brick; Ashlar
Fire test - Critical Radiant Flux – AS ISO 9239-1:2003	Class I Pass
	4.5 kW/m2
Anti-static – AATCC 134	≤3.5 kV Pass
Wear tests - Hexapod Drum Test ASTM D5252	3 Pass
Castor Chair BS EN 985	R=2.8 Pass
Stability -	1433
Delamination ASTM S3936	No Separation
Dimensional Stability AACHEN	≤0.2 Pass
Warranties -	15 Year Wear Resistance Limited Warranty
	15 Year Delamination Limited Warranty
	15 Year Dimensional Stability Limited Warranty
	15 Year Castor Chairs Limited Warranty
	15 Year Stain Limited Warranty
	Life-time Static Limited Warranty

• All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.

- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

**p** 03 366 9839 **e** office@robertmalcolm.co.nz 10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand **robertmalcolm.co.nz** 

