

Carpet Tile

Mineral


Specifications:



Solution dyed nylon



Antistatic covering



Fade resistant



Castor wheel resistant



Construction -	Multi-level Loop
Fibre -	100% Solution Dyed Nylon
Gauge -	1/12"
Stitches -	10 per inch
Pile weight -	23 oz/yd ²
Average pile height -	4 mm ± 0.5 mm
Backing -	PVC with Fiberglass
Tile size -	50 cm x 50 cm
Traffic classification -	Class II, Heavy Commercial
Antimicrobial -	Ultra-Fresh
Installation method -	Quarter Turn; Monolithic; Brick; Ashlar
Fire test -	Class I Pass
Critical Radiant Flux AS ISO 9239-1:2003 -	4.5 kW/m ²
Anti-static AATCC134 -	≤3.5 kV Pass
Wear tests	
Hexapod drum test ASTM D5252 -	3 Pass
Castor chair BS EN985 -	R =2.8 Pass
Stability	
Delamination ASTM D3936 -	No Separation
Dimensional stability AACHEN -	≤ 0.2
Warranties -	
	15 Year Wear Resistance Limited Warranty
	15 Year Delamination Limited Warranty
	15 Year Dimensional Stability Limited Warranty
	15 Year Castor Chairs Limited Warranty
	15 Year Stain Limited Warranty
	Life-time Static Limited Warranty

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under castor wheels to protect the appearance retention of the product and to avoid excessive wear in these areas.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz

robert malcolm

