

Residential Vinyl Zest


Specifications:




Domestic
light



Slip
resistant



Reduces
noise




Light
fastness



Thermal
resistance



Chemical
resistant



Stocked in
New Zealand



European classification EN ISO 10874 -	21
Total thickness -	1.50 mm
Wear layer -	0.20 mm
Total weight -	1210 g/m ²
Width -	2 m & 3 m
Slip resistance DIN 51130 -	R10
Inflammability EN 13501-1 -	Cfl-S1
Critical radiant flux ISO 9239.1:2010 -	
Acoustical insulation -	12 dB
Light fastness -	≥ 6
Underfloor heating -	Suitable
Thermal resistance -	0.02 m ² /kW
Resistance to household chemicals -	OK
Residual indentation EN ISO 24343-1 -	≤ 0.25 mm
Dimensional stability EN ISO 23999 -	≤ 0.15
Formaldehyde group EN 717-1 -	E1
Total VOC emissions EN 16516 -	Gold
Warranty (year) -	5 years (Residential use)

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

