### Solution Dyed Nylon – PVC Backed Carpet Tiles

### **BPIR Declaration**

Version 2.0 April 2024

Designated Building Product: Class 1

### Declaration

Robert Malcolm Limited has provided this declaration to satisfy the provisions of Schedule 1 (d) of the Building (Building Product Information Requirements) Regulations 2022. See <u>Regulations</u>

### **Company Details**

Name:	Robert Malcolm Limited
Role:	Supplier
NZBN:	9429031999632
Address:	10 Establishment Drive, Hornby South, Christchurch 8042
Website:	www.robertmalcolm.co.nz
Email:	office@robertmalcolm.co.nz
Phone:	03 366 9839
Manufacturer:	OFC Carpet Co. Ltd <u>www.ofc-carpet.com</u>

### **Description of the Building Product**

Robert Malcolm carpet tiles (refer product summary below) are commercial grade, with multi-level loop pile construction comprising of solution dyed nylon face yarn, polypropylene primary backing, latex layer and secondary PVC (*polyvinyl chloride*) backing. Carpet tiles are generally installed by fixing the carpet tile to the substrate with adhesive, these products are suitable for installation on stairs when used in conjunction with a compatible stair nosing.

Robert Malcolm carpet tiles are available in a range of formats that vary in design and size – please refer to the product summary below.

Name	Dimensions	Pack Size	Wear Warranty Commercial Use
Токуо	Tile - 50 x 50cm	20 Tiles / 5m2 per box	15 years
Sydney	Tile - 50 x 50cm	20 Tiles / 5m2 per box	15 years
Rome	Tile – 50 x 50cm	20 Tiles / 5m2 per box	15 years

### **Moduleo Product Summary**

### Sustainability

OFC Carpet Co. Ltd, the manufacturer, considers the sustainability of their products and business practices by actively engaging in the following:

• Green Label Plus

robert malcolm

# **Building Code Obligations**

# **B2** Durability

B2.3.1 (c)

Building elements must, with only normal maintenance continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated or:

(c) 5 years if

(i) the building elements (including services, linings, renewable protective coatings and fixtures) are easy to access and replace, and

(ii) failure of those building elements to comply with the building code would be easily detected during normal use of the building

Evidence	Rationale		
Traffic Classification	Commercial Heavy Duty		
	Robert Malcolm Limited provide the following warranty on solution		
	dyed nylon, PVC backed products:		
	-15 year wear resistance warranty		
	-15 year dimensional stability warranty		
	-15 delamination warranty		
	-15 year castor chair warranty		
	-15 year stain warranty		
	-Lifetime static warranty		
	Further test results within the product specification sheet		
	demonstrating evidence of durability during normal use of the product.		
Wear Tests			
Castor Chair EN 985:2001	Pass r = 2.4		
B2/VM1 1.1.1 In-service history	OFC Carpet Co. products have been manufactured since 2003 in China,		
	they hold ISO 9001 quality management system certification.		
	This activities the newformer new increases of the Duilding Code for a		
	This satisfies the performance requirements of the Building Code for a		
	period of 5 years as the floor covering is easy to access and replace, and failure of the product would be easily detected during normal use		
	of the product.		

C3 Fire affecting areas beyond the fire source					
		e following areas of building	s must meet the perform	ance criteria	
specified below					
Area of Building		Minimum critical radiant flux when tested to ISO 9239-1:2010			
		Buildings not protected with a	n Buildings protected wit	n an automatic fire	
		automatic fire sprinkler system			
Sleeping areas and exitways in		4.5 kW/m2	2.2 kW/m2		
buildings where care or detention is					
provided					
Exitways in all other buildings		2.2 kW/m2	2.2 kW/m2		
Firecells accommodating more than		2.2 kW/m2	1.2 kW/m2		
50 persons					
All other occupie	d spaces except	1.2 kW/m2	1.2 kW/m2		
household units					
<b>F</b> ordal and a		Detionals			
Evidence	Overlite to the	Rationale		h +	
=	Quality Inspection	Tianjin Product Quality Ins			
Technology Res		engaged by OFC Carpet Co	-	-	
Carpet Researc		Test results on these produ		eter to the table	
GB/T 11785 – 2		below and supporting docu			
Or BS EN ISO 92	239-1:2010	Test results confirm that the	e performance requireme	ents outlined in the	
		table above are satisfied.			
Range	Date of Test	Test Number	Mean Critical Ra	adiant Flux	
Токуо	16/10/2023	XS-2023-040	8.2 kW/m2		
Sydney	16/10/2023	XS-2023-039	7.6 kW/m2		
Rome	25/03/2024	WT-2024-113	≥8.8 kW/m2		
D1 Access Rout	es				
D1.3.3(d) Acces	s routes shall:				
-Have adequate	e slip resistant walkir	ig surfaces under all condition	ns of normal use		
-		cluding level accessible rout		vet with water in	
	lking surfaces shall e	_			
	-	of not less than 39 from the	wet pendulum test metho	od of AS 4586	
-	dix A using the Slider				
	-	Table 2 as 'acceptable wet sl	ip'		
-,			P.		
Table 2: Slip Re	sistance for Walking	s Surfaces			
Walking Surfac	e	Level Surface	Sloping Su	rface or Stairs	
		Acceptable Accepta	ble Acceptable	Acceptable	
		dry slip wet slip	-	wet slip	
		resistance resistar		resistance	
Carpet					
Tufted or Loon F	Pile	Yes Yes	Yes	Yes	
Tufted or Loop F	Pile	Yes Yes	Yes	Yes	
	Pile		Yes	Yes	
Evidence		Rationale			
		<b>Rationale</b> Table 2 above confirms tha	t OFC products listed in tl	ne product	
Evidence		Rationale Table 2 above confirms tha summary meet the perform	t OFC products listed in than the second s	ne product Building Code	
Evidence		Rationale Table 2 above confirms tha summary meet the perforr D1.3.3(b) as an Acceptable	t OFC products listed in th nance requirement of the Solution under dry or we	ne product Building Code	
Evidence		Rationale Table 2 above confirms tha summary meet the perform	t OFC products listed in th nance requirement of the Solution under dry or we	ne product Building Code	
Evidence		Rationale Table 2 above confirms tha summary meet the perforr D1.3.3(b) as an Acceptable	t OFC products listed in th nance requirement of the Solution under dry or we	ne product Building Code	
Evidence		Rationale Table 2 above confirms tha summary meet the perforr D1.3.3(b) as an Acceptable	t OFC products listed in th nance requirement of the Solution under dry or we	ne product Building Code	
Evidence		Rationale Table 2 above confirms tha summary meet the perforr D1.3.3(b) as an Acceptable	t OFC products listed in th nance requirement of the Solution under dry or we	ne product Building Code	
Evidence		Rationale Table 2 above confirms tha summary meet the perforr D1.3.3(b) as an Acceptable	t OFC products listed in th nance requirement of the Solution under dry or we	ne product Building Code	
Evidence		Rationale Table 2 above confirms tha summary meet the perforr D1.3.3(b) as an Acceptable	t OFC products listed in th nance requirement of the Solution under dry or we	ne product Building Code	
Evidence		Rationale Table 2 above confirms tha summary meet the perforr D1.3.3(b) as an Acceptable	t OFC products listed in th nance requirement of the Solution under dry or we	ne product Building Code	
Evidence		Rationale Table 2 above confirms tha summary meet the perforr D1.3.3(b) as an Acceptable	t OFC products listed in th nance requirement of the Solution under dry or we	ne product Building Code	

## F2 Hazardous building materials

F2.1 The objective of this provision is to safeguard people from injury and illness caused by exposure to hazardous building materials

F2.3.1 The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

Evidence	Rationale
CRI Green Label GLP100229	Total VOC's 0.5mg/m3 or less
GLF 100223	

# Scope of Use and Limitations

# Building Work

Scope	Limitation
In conjunction with a substrate and primary	-Installation must be in accordance with Flooring
structure that complies with the NZ Building Code,	Standards AS/NZS 2455.1:1:2007 Textile
or where the primary structure is the equivalent	floorcoverings – Installation practice Part 1: General
stiffness to the framing provisions of NZS 3604: 2011	& Part 2: Carpet tiles
	-Installation must be in accordance with Floor NZ
	Best Practice Guidelines for the New Zealand
	Flooring Industry – Carpet Floor Coverings Planning
	and Installation
For all building classified uses	-For commercial and industrial uses, refer to Robert
	Malcolm Limited for warranty details and exclusions
	-Robert Malcolm carpet tiles are only suitable for
	use in interior situations that are dry under normal
	use
Stain resistance warranty	-Excludes non-food and non-beverage stains caused
	by substances such as cosmetics, bleaches, inks and
	waxes. Refer to Robert Malcolm Limited for further
	details
Suitable for installation on stairs	-A compatible stair nosing must be used for
	installation of Robert Malcolm carpet tiles on stairs

## Conditions of Use

Robert Malcolm carpet tiles must be installed and maintained in accordance with all of the Robert Malcolm requirements.

## Warning or Ban

This building product line is not subject to a warning or ban under section 26 of the Building Act 2004.

## **Additional Information**

For all design, installation and maintenance-related information, and for information supporting Robert Malcolm claims, refer to <u>www.robertmalcolm.co.nz</u>

## **Product Links**

Sydney <u>https://www.robertmalcolm.co.nz/contact-us/bpi-library/#sydney</u> Tokyo <u>https://www.robertmalcolm.co.nz/contact-us/bpi-library/#tokyo</u> Rome <u>https://www.robertmalcolm.co.nz/contact-us/bpi-library/#rome</u>