

EN READY-TO-USE GROUT FOR LUXURY VINYL TILES, WATER-REPELLENT, MOULD RESISTANT, EASY TO APPLY, EASY TO REMOVE AND CLEAN FROM THE SURFACE OF THE LVT AND SMOOTH FINISH, FOR GROUT JOINTS FROM 2 TO 5 mm •

Instructions for use - Application: make sure the adhesive used for bonding the LVT is dry. Grout joints must be clean and dry. Mix the product by hand before use. Fill the joints with FLEXCOLOR 4 LVT using a special Mapei rubber trowel. Do not leave any gaps or steps, and apply to create a smooth finish. Immediately remove excess grout by moving the edge of the float diagonally across the joint. **Cleanup and finishing:** 15 to 20 minutes after applying the grout, depending on the environmental conditions, and only once a surface skin has started to form, gently rub using a damp firm cellulose sponge, applying light pressure in a circular motion over the

C1.99810041 - MADE IN EU
Net weight
1 kg e



NL GEBRUIJKLARE VOEGPASTA
VOOR LVT VLOEREN

EN READY-TO-USE GROUT FOR LVT FLOORS

FR JOINT PRÊT À L'EMPLOI POUR LVT

DE GEBRAUCHSFERTIGE
DISPERSIONSFUGE
FÜR LVTS

Joint
Sealant



grout residue. Any traces of product still visible after a few hours may be removed with a damp Scotch-Brite® pad. **Note:** wait 24 hours prior to the final cleanup with a dry cloth, Scotch-Brite® pad or KERAPOXY CLEANER. **Set to light foot traffic:** 24-36 hours. **Ready for use:** 72 hours. **Consumption:** according to the size of the grout (for example, approx. 0.06 kg/m² for 3 mm joint width, 30x60 cm plate). **Storage:** 12 months in its original sealed packaging. Contains biocidal products: 2-octyl-2H-isothiazol-3-one. Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. For further information see the technical Data Sheet.

PRODUCT FOR PROFESSIONAL USE.
PROTECT FROM FROST.