

## Xtrafloor™ Click Stairnosings

Composition - Composition – Samenstelling – Zusammensetzung	
Composition - Composition – Samenstelling – Zusammensetzung	For LVT floor coverings from 4.0 – 5.0 mm- Profiles are made of aluminium - Pour des revêtements sols LVT – Design de 4.0 à 5.0 mm d'épaisseur - Profilés en aluminium - Voor LVT-bekledingen van 4.0 - 5.0 mm – Aluminium profielen - Für LVT-Designbeläge von 4.0 – 5.0 mm - Profile aus Aluminium
Material - Article - Artikelnummer – Artikelnummer	340235 (Inner corner - Coin intérieur - Binnenhoek - Treppenkanteninnenwinkel) 340237 (Outer corner - Coin extérieur - Buitenhoek - Treppenkantenprofil)
Colour - Couleur – Kleur – Farbe	Silver
Storage - Stockage – Stockage – Lagerung	Store cool and dry - Conserver au frais et à sec - Stockeer koel en droog - Kühl und trocken lagern

SIZE & PACKING - DIMENSIONS & EMBALLAGE - FORMAAT & VERPAKKING - ABMESSUNG & VERPACKUNG	
Packaging – Emballage – Verpakking – Verpackung	6 pieces - 6 pièces - 6 stuks - 6 Stücke
Size – Dimensions – Formaat – Abmessung	27 x 27 x 2400 mm (Inner corner - Coin intérieur - Binnenhoek - Treppenkanteninnenwinkel) 42 x 28 x 2400 mm (Outer corner - Coin extérieur - Buitenhoek - Treppenkantenprofil)

INSTALLATION – INSTALLATION – INSTALLATIE – INSTALLIERUNG	
Fasten the profile by using Xtrafloor MSK Adhesive - Fixer le profilé avec la colle Xtrafloor MSK - Bevestig het profiel met behulp van Xtrafloor MSK Lijm - Befestigen Sie das Profil mit Xtrafloor MSK Kleber	

### TECHNICAL DRAWING - DESSIN TECHNIQUE – TECHNISCHE TEKENING - TECHNISCHE ZEICHNUNG

